

IOWA STATE UNIVERSITY

Digital Repository

Tech Transfer Summaries

Institute for Transportation

10-2014

Chevrons and Oversized Chevrons

Shauna L. Hallmark

Iowa State University, shallmar@iastate.edu

Neal R. Hawkins

Iowa State University, hawkins@iastate.edu

Follow this and additional works at: http://lib.dr.iastate.edu/intrans_techtransfer



Part of the [Civil Engineering Commons](#)

Recommended Citation

Hallmark, Shauna L. and Hawkins, Neal R., "Chevrons and Oversized Chevrons" (2014). *Tech Transfer Summaries*. 69.

http://lib.dr.iastate.edu/intrans_techtransfer/69

This Report is brought to you for free and open access by the Institute for Transportation at Iowa State University Digital Repository. It has been accepted for inclusion in Tech Transfer Summaries by an authorized administrator of Iowa State University Digital Repository. For more information, please contact digirep@iastate.edu.

Chevrons and Oversized Chevrons

Abstract

Chevrons provide additional emphasis and guidance for drivers. If spaced properly, chevrons can delineate the curve so drivers can interpret the sharpness of the curve. Table 2C-2 of the *Manual on Uniform Traffic Control Devices* (FHWA 2009a) recommends the size of chevron alignment (W1-8) signs by roadway type. Several agencies, including the Iowa Department of Transportation (Iowa DOT), have applied a larger chevron size to a roadway than suggested by this table. The idea is that larger chevrons will be more prominent and visible to drivers. These larger chevrons may be particularly useful if sight distance issues exist.

Keywords

Countermeasures, Highway Safety, Ran off road crashes, Rural highways, Signs, Symbol signs, Traffic control devices, Traffic safety

Disciplines

Civil Engineering

Comments

Please note: this summary is part of the website Synthesis of Safety-Related Research <http://www.ctre.iastate.edu/research-synthesis/> which brings together a number of individual reports available in the InTrans collections in this repository.

Chevrons and Oversized Chevrons

■ Authors

Shauna L. Hallmark

Director, Institute for Transportation,
and Professor, Civil, Construction, and
Environmental Engineering,
Iowa State University
515-294-5249, shallmar@iastate.edu

Neal Hawkins

Director, Center for Transportation Research
and Education, Iowa State University

■ Sponsors

Iowa Department of Transportation
Federal Highway Administration
(InTrans Project 12-452)

■ For More Information

Center for Transportation Research and
Education
Iowa State University
2711 S. Loop Drive, Suite 4700
Ames, IA 50010-8664
515-294-8103
www.intrans.iastate.edu/

Description

Chevrons provide additional emphasis and guidance for drivers. If spaced properly, chevrons can delineate the curve so drivers can interpret the sharpness of the curve.

Table 2C-2 of the *Manual on Uniform Traffic Control Devices* (FHWA 2009a) recommends the size of chevron alignment (W1-8) signs by roadway type. Several agencies, including the Iowa Department of Transportation (Iowa DOT), have applied a larger chevron size to a roadway than suggested by this table (see Figure 1). The idea is that larger chevrons will be more prominent and visible to drivers. These larger chevrons may be particularly useful if sight distance issues exist.

Placement

Chapter 2 of the MUTCD (FHWA 2009a) covers standard application of chevrons. No standards exist for use of oversized chevrons. In general, standard chevrons signs are replaced with the next largest size specified in the MUTCD.

In contrast to chevron size, alternatives to the frequency and spacing around a curve have also been evaluated. A field study by the Texas Transportation Institute (TTI) (Rose and Carlson 2005) evaluated the impact of varying the number of chevrons in view around a curve and developed an alternate spacing chart to assist maintenance personnel.

Pratt et al. (2009) composed a table of speed based guidelines for selecting curve traffic control devices. As shown in Table 1, chevrons, large arrows, or both are required for differences between speed limit and advisory speed exceeding 15 mph. However, their use is recommended only for 10 to 14 mph differences in speed.

Effectiveness of Oversized Chevrons

The effectiveness of oversized chevrons is unknown.

Effectiveness of Chevrons

No studies have been completed in Iowa to evaluate the effectiveness of



Center for Transportation
Research and Education

IOWA STATE UNIVERSITY

Institute for Transportation



Figure 1. Oversized chevrons on US 6 in Johnson County, Iowa (Tom Welch, Iowa DOT)

Table 1. Guidelines for the Implementation of Curve Traffic Control Devices Based on Speed Differentials

Sign Type	Difference Between Speed Limit and Advisory Speed (mph)				
	5 to 9	10 to 14	15 to 19	20 to 24	≥ 25
Turn, Curve, Reverse Turn, Reverse Curve, or Winding Road	Recommended	Required	Required	Required	Required
Advisory	Recommended	Required	Required	Required	Required
Chevrons, Large Arrow, or Both	Optional	Recommended	Required	Required	Required
Horizontal Alignment/Advisory Speed at Beginning of Curve	—	—	Optional	Optional	Recommended

chevrons. A current study is being conducted involving crash modification factors for chevrons. This brief will be updated when the study is completed. Known national studies on the effectiveness of chevrons in reducing speed or crashes are summarized below.

Zador et al. (1987) evaluated the effectiveness of chevrons and other treatments at 46 sites in Georgia and five sites in New Mexico. Additionally, at several other control sites, the researchers collected lateral placement data at each curve. The authors found that, at night, drivers moved away from the centerline, and vehicle speed and placement variability were reduced slightly with the use of chevrons and raised pavement markings.

Jennings and Demetsky (1983) evaluated chevrons along several rural Virginia curves. The roadway segments had average daily traffic (ADT) between 1,000 and 3,000 vehicles per day (vpd). The researchers found that overall speed and speed variance decreased with the use of chevrons. The researchers also recommended chevron installation for curves greater than seven degrees.

Re et al. (2010) evaluated the application of chevrons and chevrons with a full-post retro reflective treatment at two curves on rural two-lane roadways in Texas. Both sites had paved shoulders and a posted speed limit of 70 mph during the day and 65 mph at night. One site had an advisory speed of 45 mph and the other had an advisory speed of 50 mph.

Each treatment was applied to each site and the researchers collected speed and lateral position before and 10 days after installation of the treatment. Average speeds with chevrons were 1.6 mph lower (see Table 2), and 85th percentile speeds decreased on average by 1.3 mph.

A pooled fund study evaluated the impact of improved curve delineation (FHWA 2009b) in the state of Washington. This study installed chevrons at sites where chevrons were not posted previously, as well as increased the number of chevrons at locations where they were already present. The authors noted a reduction in several crash types (see Table 3).

Advantages

Low cost

Disadvantages

Use of traffic control devices when not warranted can result in additional costs for maintenance and replacement

References

- FHWA. *Manual on Uniform Traffic Control Devices for Streets and Highways*. U.S. Department of Transportation, Federal Highway Administration, 2009(a).
- FHWA. Safety Evaluation of Improved Curve Delineation, Tech Brief. Report FHWA-HRT-09-046, 2009(b).
- Jennings, B. and M. Demetsky. *Evaluation of Curve Delineation Signs*. Report VHTRC 84-R16. Virginia Highway and Transport Research Council. Charlottesville, Virginia, 1983.
- Montella, Alfonso. "Safety Evaluation of Curve Delineation Improvements Empirical Bayes Observational Before-and-After Study." *Transportation Research Record: Journal of the Transportation Research Board* 2103 (2009): 69-79.
- Pratt, Michael P., and James A. Bonneson. "Assessment of Traffic Control Device Selection Guidelines for Horizontal Curves." *Transportation Research Record* 2122 (2009): 36-44. Transportation Research Board. Accessed October 25, 2013. trb.metapress.com/content/4250033lm8750567/fulltext.pdf
- Re, Jonathan M., H. Gene Hawkins, Jr., and Susan T. Chrysler. "Assessing Benefits of Chevrons with Full Retro reflective Signposts on Rural Horizontal Curves." *Transportation Research Record: Journal of the Transportation Research Board* 2149 (2010): 30-36.
- Rose, Elisabeth R. and Paul J. Carlson. "Spacing Chevrons on Horizontal Curves." *Transportation Research Record: Journal of the Transportation Research Board* 1918 (2005): 84-91.

Table 2. Speed Results for Chevrons (Re et al. 2010)

Site	Advisory speed (mph)	Mean speed (mph)			85th percentile speed (mph)		
		Before	After	Change	Before	After	Change
1	45	58.3	56.8	-1.5	65.7	64.2	-1.5
2	50	54.8	53.2	-1.6	64.2	63.1	-1.1
Average		56.6	55.0	-1.6	65.0	63.7	-1.3

Table 3. CMFs for Chevrons

Sign Type	Crash Type	CMF
Chevron and curve warning signs (Montella 2009)	All crashes on principal arterial/freeways/expressways	0.59
	ROR rashes on principal arterial/freeways/expressways	0.56
	Fatal/serious injury/minor injury	1.46
	Nighttime	0.66
Chevron signs (Montella 2009; Srinivasan et al. 2009)	All crashes on principal arterial/freeways/expressways	0.63 to 1.27
	ROR crashes on principal arterial/freeways/expressways	0.90
	Property damage only on principal arterial/freeways/expressways	0.83
	Fatal and injury crashes on principal arterial/freeways/expressways	1.46
	Nighttime on principal arterial/freeways/expressways	1.92
	Wet road crashes on principal arterial/freeways/expressways	0.41
	All crashes on rural two-lane	0.96
	Head-on/sideswipe on rural two-lane	0.94
	Fatal and injury crashes on rural two-lane	0.84
	Nighttime on rural two-lane	0.75
	Nighttime head-on/sideswipe on rural two-lane	0.78

Srinivasan, R., J. Baek, D. Carter, B. Persaud, C. Lyon, K. Eccles, F. Gross, and N. Lefler. *Safety Evaluation of Improved Curve Delineation*. Report FHWA-HRT-09-045. Federal Highway Administration, Washington, DC, 2009.

Zador, P., H. S. Stein, P. Wright, and J. Hall. "Effects of Chevrons, Post-Mounted Delineators, and Raised Pavement Markers on Driver Behavior at Roadway Curves." *Transportation Research Record: Journal of the Transportation Research Board* 1114 (1987).

Other Resources

Chrysler, Susan T., Jon Re, Keith S. Knapp, Dillon S. Funkhouser, and Beverly T. Kuhn. *Driver Response to Delineation Treatments on Horizontal Curves on Two-Lane Roads*. Report FHWA/TX-09/-5772-1. Texas Transportation Institute, 2009.

McGee, Hugh W., and Fred R. Hanscom. *Low-Cost Treatments for Horizontal Curve Safety*. Report FHWA-SA-07-002. Federal Highway Administration, Washington, DC, 2006.

About the Center for Transportation Research and Education

The mission of the Center for Transportation Research and Education (CTRE) at Iowa State University is to develop and implement innovative methods, materials, and technologies for improving transportation efficiency, safety, reliability, and sustainability while improving the learning environment of students, faculty, and staff in transportation-related fields.

The sponsors of this research are not responsible for the accuracy of the information presented herein. The conclusions expressed in this publication are not necessarily those of the sponsors.

Iowa State University does not discriminate on the basis of race, color, age, ethnicity, religion, national origin, pregnancy, sexual orientation, gender identity, genetic information, sex, marital status, disability, or status as a U.S. veteran. Inquiries regarding non-discrimination policies may be directed to Office of Equal Opportunity, Title IX/ADA Coordinator, and Affirmative Action Officer, 3350 Beardshear Hall, Ames, Iowa 50011, 515-294-7612, email eooffice@iastate.edu.